

# BLMC - AUSTIN HEALEY

Application	Engine	Cyl	Years	Set Number		Line No
	Model	Bore		CC	Chrome	
100-4		87.30	2660	48-56		<b>P1003</b> 12
100-4 (5-Ring Replc.)		87.30	948			<b>P1135</b> 13
100-6		79.37	2639	58-59		<b>P1008</b> 8
100-6 (5-Ring Replc.)		79.37	948			<b>P1228</b> 9
1100 Sprite	ADO16	64.60	1098	62-70	<b>C1072</b>	<b>P1072</b> 5
3000 MK I, II, III	BMC-C	83.33	2912	57-67		<b>P1098</b> 10
3000 MK I, II, III (5-Ring Replc.)		83.33	2612			<b>P1230</b> 11
Sprite MK I	AN5	62.93	948	57-62	<b>C1058</b>	<b>P1058</b> 1
Sprite MK I		62.93	948	57-62		<b>P1822</b> 4
Sprite MK I, II (3-Ring Replc.)		62.93	948			<b>P1133</b> 2
Sprite MK I, II (5-Ring Replc.)		62.93	948			<b>P1225</b> 3
Sprite MK II	AN6	62.93	948	57-62	<b>C1058</b>	<b>P1058</b> 1
Sprite MK II, III	10F	64.60	1098	63-68	<b>C1072</b>	<b>P1072</b> 5
Sprite MK II, III, 1100 Sprite (5-Ring Replc.)		64.60	948		<b>C1349</b>	<b>P1349</b> 6
Sprite MK IV	12G	70.61	1275	67-70	<b>C1280</b>	<b>P1280</b> 7

Line No	Application	CC	Set No	Cyl	Bore Diameter		Ring Size	
					Inch	MM	Comp	Oil
1	Sprite MK I Sprite MK II	(.9L) 948	<b>P1058</b> <b>C1058</b>	4	2.478	62.93	4 - .070" 4 - .070" 4 - .070"	4 - .125"
2	Sprite MK I, II (3-Ring Replc.)	(.9L) 948	<b>P1133</b>	4	2.478	62.93	4 - 1.60 4 - 1.60	4 - 3.17
3	Sprite MK I, II (5-Ring Replc.)	(.9L) 948	<b>P1225</b>	4	2.478	62.93	4 - .070" 4 - .070" 4 - .070"	4 - .125" 4 - .125"
4	Sprite MK I	(.9L) 948	<b>P1822</b>	4	2.478	62.93	4 - .070" 4 - .070" 4 - .070"	4 - .157"
5	Sprite MK II, III 1100 Sprite	(1.1L) 1098	<b>P1072</b> <b>C1072</b>	4	2.542	64.60	4 - 1/16 4 - 1/16 4 - 1/16	4 - 1/8
6	Sprite MK II, III, 1100 Sprite (5-Ring Replc.)	(.9L) 948	<b>P1349</b> <b>C1349</b>	4	2.542	64.60	4 - 1.60 4 - 1.60 4 - 1.60	4 - 3.17 4 - 3.17
7	Sprite MK IV	(1.3L) 1275	<b>P1280</b> <b>C1280</b>	4	2.780	70.61	4 - 1/16 4 - 1/16 4 - 1/16	4 - 5/32
8	100-6	(2.6L) 2639	<b>P1008</b>	6	3.125	79.37	6 - 3/32 6 - 3/32 6 - 3/32	6 - 3/16
9	100-6 (5-Ring Replc.)	(.9L) 948	<b>P1228</b>	6	3.125	79.37	6 - 2.38 6 - 2.38 6 - 2.38	6 - 4.75 6 - 4.75
10	3000 MK I, II, III	(3.0L) 2912	<b>P1098</b>	6	3.281	83.33	6 - 3/32 6 - 3/32 6 - 3/32	6 - 3/16
11	3000 MK I, II, III (5-Ring Replc.)	(3.0L) 2612	<b>P1230</b>	6	3.281	83.33	6 - 2.38 6 - 2.38 6 - 2.38	6 - 4.75 6 - 4.75
12	100-4	(2.7L) 2660	<b>P1003</b>	4	3.437	87.30	4 - 3/32 4 - 3/32 4 - 3/32	4 - 5/32

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone

# BLMC - AUSTIN HEALEY

Line						Bore Diameter		Ring Size	
No	Application		CC	Set No	Cyl	Inch	MM	Comp	Oil
13	100-4 (5-Ring Replc.)	(.9L)	948	P1135	4	3.437	87.30	4 - 2.38	4 - 4.00
								4 - 2.38	4 - 4.00
								4 - 2.38	

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone