

BLMC - AUSTIN

Application	Engine	Cyl			Set Number		Line
	Model	Bore	CC	Years	Chrome	Plain	No
1300	12G	70.61	1275	68-72	C1280	P1280	14
1300 Mk V (USA)	A Series	70.61	1275	72-73	C5230	P5230	18
1800 MK II, III	18V	80.25	1798	72-74	C1338	P1338	28
1800, 1800s MK I, II	ADO17	80.25	1798	64-71	C1175	P1175	27
850 Mini	ADO15	62.93	848	59-75	C1058	P1058	2
A35, A40	ADO15	62.93	848	57-62	C1058	P1058	2
A35, A40 Mini Seven, 850 Mini (3-Ring Replc.)		62.93				P1133	3
A35, A40 Mini Seven, 850 Mini (5-Ring Replc.)		62.93				P1225	4
A40		65.50	1198	53-57		P1961 ^A	10
A40 Mk II	ADO16	64.60	1098	63-67	C1072	P1072	6
A40 Mk II, Mini Cooper (5-Ring Replc.)		64.60			C1349	P1349	8
A40, Moke, Princess	A	64.60	1098	62-81	C5167		5
A50, A55	B	73.03	1489	55-62	C1971	P1971	20
A50, A55 (5-Ring Replc.)		73.03			C1227	P1227	19
A60 Cambridge		76.20	1622	62-69	C1074	P1074	22
A60 Cambridge (5-Ring Replc.)		76.20			C1543	P1543	23
A70		79.37	2199	54-63		P1006	24
A90		87.30	2660	48-56		P1003	34
A90 (5-Ring Replc.)		87.30				P1135	35
A90, A95, A105		79.37	2639	55-59		P1008	25
A90, A95, A105 (5-Ring Replc.)		79.37				P1228	26
A99, A110	BMC-C	83.33	2912	59-70		P1098	30
A99, A110 (5-Ring Replc.)		83.33				P1230	31
Allegro	12G	70.61	1275	74-81	C1280	P1280	14
Allegro 1000	A Series	64.60	998	81-82	C5045	P5045	9
Allegro 1300	A Series	70.61	1275	74-83	C5230	P5230	18
Cambridge	A60	76.20	1622	62-69	C1637		21
Healey-Sprite Mk IV	A Series	70.61	1275	67-72	C5230	P5230	18
Marina GT	18V	80.25	1798	72-80	C1338	P1338	28
Marina GT, 1800 Mk II & III (5-Ring Replc.)		80.25	1800	63-71		P1396	29
Metro 1.0 City, City L 1.0, City X 1.0	A Series	64.60	998	80-90	C5045	P5045	9
Mini 1.0 City E	A Series	64.60	998	85-92	C5045	P5045	9
Mini 1000	A Series	64.60	998	75-82	C5045	P5045	9
Mini 1275 GT	A Series	70.61	1275	70-83	C5230	P5230	18
Mini 95 Pick-up, 95 Van	A Series	64.60	998	77-83	C5045	P5045	9
Mini Clubman	A Series	64.60	998	59-75	C5045	P5045	9
Mini Cooper		62.40	997	61-63		P1236	1
Mini Cooper	99H	64.60	998	64-69	C1072	P1072	7
Mini Cooper S		70.61	970	64-65	C1715 ⁺		11
Mini Cooper S		70.61	1071	63-64	C1715 ⁺		12
Mini Cooper S		70.61	1275	64-71	C1715 ⁺		13
Mini Cooper S		70.61	1071	63-64	C1385	P1385	15
Mini Cooper S		70.61	1275	63-73	C1818	P1818	17
Mini Seven	ADO15	62.93	848	59-75	C1058	P1058	2
Mk V America	12G	70.61	1275	68-72	C1280	P1280	14
Princess 1300	A Series	70.61	1275	67-74	C5230	P5230	18
Seven		62.40	997	61-63		P1236	1
Three Litre	C	83.33	2912	68-71		P1368	32
Three Litre (5-Ring Replc.)		83.33				P1397	33
With 1/16 Comp. Rings Only		70.61	1275	63-69	C1385	P1385	16

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone

BLMC - AUSTIN

Line No	Application		CC	Set No	Cyl	Bore Diameter		Ring Size	
						Inch	MM	Comp	Oil
1	Mini Cooper Seven	(1.0L)	997	P1236	4	2.458	62.40	4 - 1.60 4 - 1.60 4 - 1.60	4 - 3.17
2	A35, A40 850 Mini Mini Seven	(.8L)	848	P1058 C1058	4	2.478	62.93	4 - .070" 4 - .070" 4 - .070"	4 - .125"
3	A35, A40 Mini Seven, 850 Mini (3-Ring Replc.)			P1133	4	2.478	62.93	4 - 1.60 4 - 1.60	4 - 3.17
4	A35, A40 Mini Seven, 850 Mini (5-Ring Replc.)			P1225	4	2.478	62.93	4 - .070" 4 - .070" 4 - .070"	4 - .125" 4 - .125"
5	A40, Moke, Princess	(1.1L)	1098	C5167	4	2.542	64.60	4 - 1.60 4 - 2.00	4 - 4.00
6	A40 Mk II	(1.1L)	1098	P1072 C1072	4	2.542	64.60	4 - 1/16 4 - 1/16 4 - 1/16	4 - 1/8
7	Mini Cooper	(1.0L)	998	P1072 C1072	4	2.542	64.60	4 - 1/16 4 - 1/16 4 - 1/16	4 - 1/8
8	A40 Mk II, Mini Cooper (5-Ring Replc.)			P1349 C1349	4	2.542	64.60	4 - 1.60 4 - 1.60 4 - 1.60	4 - 3.17 4 - 3.17
9	Metro 1.0 City, City L 1.0, City X 1.0 Allegro 1000 Mini Clubman Mini 1000 Mini 95 Pick-up, 95 Van Mini 1.0 City E	(1.0L)	998	P5045 C5045	4	2.542	64.60	4 - 1/16 4 - 1/16 4 - 1/16	4 - 4.00
10	A40	(1.2L)	1198	P1961 ^A	4	2.579	65.50	4 - 5/64 4 - 5/64 4 - 5/64	4 - 5/32
11	Mini Cooper S	(1.0L)	970	C1715 ⁺	4	2.780	70.61	4 - 1.20 4 - 1.20 4 - 1.20	4 - 4.00
12	Mini Cooper S	(1.1L)	1071	C1715 ⁺	4	2.780	70.61	4 - 1.20 4 - 1.20 4 - 1.20	4 - 4.00
13	Mini Cooper S	(1.3L)	1275	C1715 ⁺	4	2.780	70.61	4 - 1.20 4 - 1.20 4 - 1.20	4 - 4.00
14	1300 Mk V America Allegro	(1.3L)	1275	P1280 C1280	4	2.780	70.61	4 - 1/16 4 - 1/16 4 - 1/16	4 - 5/32
15	Mini Cooper S	(1.1L)	1071	P1385 C1385	4	2.780	70.61	4 - 1/16 4 - 1/16	4 - 5/32
16	With 1/16 Comp. Rings Only	(1.3L)	1275	P1385 C1385	4	2.780	70.61	4 - 1/16 4 - 1/16	4 - 5/32
17	Mini Cooper S	(1.3L)	1275	P1818 C1818	4	2.780	70.61	4 - 1.50 4 - 1.50	4 - 3.00
18	Mini 1275 GT Healey-Sprite Mk IV Princess 1300 1300 Mk V (USA) Allegro 1300	(1.3L)	1275	P5230 C5230	4	2.780	70.61	4 - 1.50 4 - 1.50	4 - 4.00

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone

BLMC - AUSTIN

Line No	Application	CC	Set No	Cyl	Bore Diameter		Ring Size	
					Inch	MM	Comp	Oil
19	A50, A55 (5-Ring Replc.)		P1227 C1227	4	2.875	73.03	4 - 5/64 4 - 5/64 4 - 5/64	4 - 5/32 4 - 5/32
20	A50, A55 (1.5L)	1489	P1971 C1971	4	2.875	73.03	4 - 5/64 4 - 5/64 4 - 5/64	4 - 5/32
21	Cambridge (1.6L)	1622	C1637	4	3.000	76.20	4 - 2.00 4 - 2.00	4 - 4.75 4 - 4.75
22	A60 Cambridge (1.6L)	1622	P1074 C1074	4	3.000	76.20	4 - 5/64 4 - 5/64 4 - 5/64	4 - 5/32
23	A60 Cambridge (5-Ring Replc.)		P1543 C1543	4	3.000	76.20	4 - 5/64 4 - 5/64 4 - 5/64	4 - 5/32 4 - 5/32
24	A70 (2.2L)	2199	P1006	4	3.125	79.37	4 - 3/32 4 - 3/32 4 - 3/32	4 - 3/16
25	A90, A95, A105 (2.6L)	2639	P1008	6	3.125	79.37	6 - 3/32 6 - 3/32 6 - 3/32	6 - 3/16
26	A90, A95, A105 (5-Ring Replc.)		P1228	6	3.125	79.37	6 - 2.38 6 - 2.38 6 - 2.38	6 - 4.75 6 - 4.75
27	1800, 1800s MK I, II (1.8L)	1798	P1175 C1175	4	3.160	80.25	4 - 1/16 4 - 1/16 4 - 1/16	4 - 5/32
28	1800 MK II, III Marina GT (1.8L)	1798	P1338 C1338	4	3.160	80.25	4 - 1.60 4 - 1.60	4 - 4.00
29	Marina GT, 1800 Mk II & III (5-Ring Replc.) (1.8L)	1800	P1396	4	3.160	80.25	4 - 1.60 4 - 1.60 4 - 1.60	4 - 4.00 4 - 4.00
30	A99, A110 (2.9L)	2912	P1098	6	3.281	83.33	6 - 3/32 6 - 3/32 6 - 3/32	6 - 3/16
31	A99, A110 (5-Ring Replc.)		P1230	6	3.281	83.33	6 - 2.38 6 - 2.38 6 - 2.38	6 - 4.75 6 - 4.75
32	Three Litre (2.9L)	2912	P1368	6	3.281	83.33	6 - 2.00 6 - 2.00 6 - 2.00	6 - 4.75
33	Three Litre (5-Ring Replc.)		P1397	6	3.281	83.33	6 - 2.00 6 - 2.00 6 - 2.00	6 - 4.75 6 - 4.75
34	A90 (2.7L)	2660	P1003	4	3.437	87.30	4 - 3/32 4 - 3/32 4 - 3/32	4 - 5/32
35	A90 (5-Ring Replc.)		P1135	4	3.437	87.30	4 - 2.38 4 - 2.38 4 - 2.38	4 - 4.00 4 - 4.00

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone