

GENERAL MOTORS

Cubic Inch	Year	Application	Set No	Cyl	Bore Diameter		Ring Size	
					Inch	MM	Comp	Oil
	2002	(1.0L) GMB VHC	S5300^N	4	2.800	71.08	4 - 1.20 4 - 1.50	4 - 2.00
61	85-00	(1.0L) GMC Sprint (Suzuki eng.) Incl Turbo	C1585⁺	3	2.913	74.00	3 - 1.20	3 - 2.80
61	89-92	(1.0L) Geo Metro (Suzuki eng.)					3 - 1.50	
61	87-88	(1.0L) Geo Sprint (Turbo)						
61	89-95	(1.0L) Geo Metro 2 Ring Piston (Suzuki eng.)	C3888⁺	3	2.913	74.00	3 - 1.20	3 - 2.80
79	90-97	(1.3L) Geo Metro (Suzuki eng.) 9	C3908⁺	4	2.913	74.00	4 - 1.20 4 - 1.50	4 - 2.80
79	98-01	(1.3L) Geo Metro G13KS, 2, 9	C5013⁺	4	2.913	74.00	4 - 1.20 4 - 1.20	4 - 2.50
85	76-77	(1.4L) Chevrolet Chevette I	P1411 C1411	4	3.228	82.00	4 - 2.00 4 - 2.00	4 - 4.00
97	89-96	(1.6L) Geo Tracker (Suzuki eng.) G16	C1676⁺	4	2.953	75.00	4 - 1.20 4 - 1.50	4 - 2.80
98	88-93	(1.6L) Pontiac LeMans (Daewoo eng.)	C1796⁺	4	3.110	79.00	4 - 1.20 4 - 1.50	4 - 3.00
98	90-95	(1.6L) Geo Storm (Isuzu eng.)	C1768⁺	4	3.150	80.00	4 - 1.20 4 - 1.20	4 - 3.00
98	90-92	(1.6L) Geo Prizm, Chevrolet (Toyota eng.)	C1784⁺	4	3.189	81.00	4 - 1.20 4 - 1.50	4 - 2.80
98	93-97	(1.6L) Geo Prizm (Toyota eng.) 4AFE, 6	C3907⁺	4	3.189	81.00	4 - 1.20 4 - 1.50	4 - 3.00
98	85-88	(1.6L) Chevrolet Nova (Toyota eng.) 4AC	P1537 C1537	4	3.189	81.00	4 - 1.50 4 - 1.50	4 - 2.80
98	89-92	(1.6L) Geo Prizm (Toyota eng.) 6	P1785	4	3.189	81.00	4 - 1.50	4 - 3.00
98	90-92	(1.6L) Geo Prizm GSi (Toyota eng.)	C1785				4 - 1.50	
98	76-83	(1.6L) Chevrolet Chevette	P1431	4	3.228	82.00	4 - 1.50	4 - 4.00
98	81-84	(1.6L) Pontiac T1000 LX5	C1431				4 - 1.50	
98	84-87	(1.6L) Chevrolet Chevette, Pontiac T1000 (Shallow Oil Ring Groove)	P1612 C1612	4	3.228	82.00	4 - 1.50 4 - 1.50	4 - 4.00
110	98-05	(1.8L) Geo Prizm, (Toyota eng.) 1ZZFE, L, 8	C5015⁺	4	3.110	79.00	4 - 1.20 4 - 1.20	4 - 3.00
110	93-97	(1.8L) Geo Prizm (Toyota eng.) 7AFE, 8	C3907⁺	4	3.189	81.00	4 - 1.20 4 - 1.50	4 - 3.00
110	04-05	(1.8L) Optra LS, MPFI L79	S5328^N	4	3.213	81.60	4 - 1.50 4 - 1.50	4 - 3.00
110	72-80	(1.8L) Chevrolet Luv Pick-Up (Gas) G180	P1331 C1331	4	3.307	84.00	4 - 2.00 4 - 2.00	4 - 4.00
110	82-83	(1.8L) Pontiac T1000 (Diesel)	P1495	4	3.307	84.00	4 - 2.50	4 - 4.00
110	82-84	(1.8L) Pontiac (Diesel)	C1495				4 - 2.00	
110	81-82	(1.8L) Chevrolet Luv Pick-Up (Gas)	P1601 C1601	4	3.307	84.00	4 - 1.50 4 - 1.50	4 - 4.00
112	82-86	(1.8L) Buick, Cadillac, Chevrolet, Oldsmobile, Pontiac OHC Incl Turbo O	P3841 C3841	4	3.339	84.80	4 - 1.50 4 - 1.75	4 - 4.00
112	81-82	(1.8L) Buick, Cadillac, Chevrolet, Oldsmobile, Pontiac	P3831 C3831	4	3.504	89.00	4 - 1.50 4 - 2.00	4 - 4.75
116	95-98	(1.9L) Saturn 7, 8	C1952⁺	4	3.228	82.00	4 - 1.20 4 - 1.50	4 - 3.00
116	99-02	(1.6L) Saturn SC, SL, SW series 7, 8	C5016⁺	4	3.228	82.00	4 - 1.20 4 - 1.50	4 - 2.50
116	91-94	(1.9L) Saturn 9	P1695 C1695	4	3.228	82.00	4 - 1.50 4 - 1.50	4 - 3.00
119	1982	(1.9L) Chevrolet S-10, GMC S-15	P1523 C1523	4	3.425	87.00	4 - 2.00 4 - 2.00	4 - 4.00

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone

GENERAL MOTORS

Cubic Inch	Year	Application	Set No	Cyl	Bore Diameter		Ring Size	
					Inch	MM	Comp	Oil
119	83-85	(1.9L) Chevrolet S-10, GMC S-15	P1554 C1554	4	3.425	87.00	4 - 1.50 4 - 1.50	4 - 4.00
121	87-91	(2.0L) Buick, Chevrolet, Oldsmobile, Pontiac Incl Turbo K, M	P1697 C1697	4	3.386	86.00	4 - 1.50 4 - 1.50	4 - 3.00
121	83-84	(2.0L) Chevrolet S-10, GMC S-15	P3831 C3831	4	3.504	89.00	4 - 1.50 4 - 2.00	4 - 4.75
121	82-89	(2.0L) Chevrolet	P3842	4	3.504	89.00	4 - 1.50	4 - 4.75
121	82-84	(2.0L) Buick, Cadillac, Oldsmobile, Pontiac	C3842				4 - 1.50	
121	85-86	(2.0L) Buick, Chevrolet, Oldsmobile, Pontiac (Shallow Oil Ring Groove)	P3851 C3851	4	3.504	89.00	4 - 1.50 4 - 1.50	4 - 4.75
121	82-84	(2.0L) Chevrolet S-10, GMC S-15	P3858 C3858	4	3.504	89.00	4 - 5/64 4 - 5/64	4 - 3/16
121	87-89	(2.0L) Chevrolet, Oldsmobile (Shallow Oil Ring Groove) 1	P3859 C3859	4	3.504	89.00	4 - 1.50 4 - 1.50	4 - 3.00
121	87-94	(2.0L) Pontiac (Shallow Oil Ring Groove) 1						
122	99-04	(2.0L) Chevrolet Tracker (Suzuki eng.) C	C3940 ⁺	4	3.307	84.00	4 - 1.20 4 - 1.50	4 - 2.50
122	75-76	(2.0L) Chevrolet	P3806 C3806	4	3.500	88.90	4 - 5/64 4 - 5/64	4 - 3/16
134		(2.2L) Chevrolet Cavalier	P3910	4	3.465	88.00	4 - 1.50 4 - 1.50	4 - 3.00
134	87-05	(2.2L) Chevrolet (Shallow Oil Ring Groove) 1, 4, 5, 6	P3859	4	3.504	89.00	4 - 1.50	4 - 3.00
134	87-89	(2.2L) Buick, Cadillac (Shallow Oil Ring Groove) 1, 4, 5, 6	C3859				4 - 1.50	
140	1960	(2.3L) Chevrolet Corvair	P2223 C2223	6	3.375	85.70	6 - 5/64 6 - 5/64	6 - 3/16
140	71-77	(2.3L) Chevrolet, Oldsmobile, Pontiac CAUTION: Only For C.I. Sleeved Engines	P3806 C3806	4	3.500	88.90	4 - 5/64 4 - 5/64	4 - 3/16
140	88-95	(2.3L) Buick/Oldsmobile/Pontiac Quad-4	P3861 C3861	4	3.622	92.00	4 - 1.50 4 - 1.50	4 - 3.00
145	61-63	(2.4L) Chevrolet Corvair	P2134 C2134	6	3.437	87.30	6 - 5/64 6 - 5/64	6 - 3/16
145	06-08	(2.4L) Cobalt, HHR Vin: B, P	S3970 ^{+N}	4	3.465	88.00	4 - 1.20 4 - 1.50	4 - 2.50
146	96-00	(2.4L) Chevrolet T	C3906 ⁺	4	3.543	90.00	4 - 1.20	4 - 3.00
146	96-02	(2.4L) Oldsmobile T					4 - 1.50	
151	77-80	(2.5L) Chevrolet V	P3819	4	4.000	101.60	4 - 5/64	4 - 3/16
151	77-78	(2.5L) Buick, Oldsmobile, Pontiac	C3819				4 - 5/64	
151	79-81	(2.5L) Buick, Chevrolet, Oldsmobile, Pontiac (Shallow Oil Ring Groove)	P3835 C3835	4	4.000	101.60	4 - 5/64 4 - 5/64	4 - 3/16
151	82-93	(2.5L) Chevrolet (Shallow Oil Ring Groove)	P3836	4	4.000	101.60	4 - 1/16	4 - 3/16
151	82-91	(2.5L) Buick, Oldsmobile, Pontiac (Shallow Oil Ring Groove)	C3836				4 - 5/64	
151	82-93	(2.5L) Buick, Oldsmobile, Pontiac	P3884 C3884	4	4.000	101.60	4 - 1.60 4 - 2.00	4 - 4.75
153	62-70	(2.5L) Chevrolet	P2238 C2238	4	3.875	98.40	4 - 5/64 4 - 5/64	4 - 3/16
164	64-69	(2.7L) Chevrolet Corvair	P2242 C2242	6	3.437	87.30	6 - 1/16 6 - 1/16	6 - 1/8
170	05-08	(2.8L) Cadillac CTS	S3972 ^{+N}	6	3.504	89.00	6 - 1.20 6 - 1.50	6 - 3.00
173	80-81	(2.8L) Buick, Chevrolet, Oldsmobile, Pontiac	P3829 C3829	6	3.504	89.00	6 - 5/64 6 - 5/64	6 - 3/16

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone

GENERAL MOTORS

Cubic Inch	Year	Application	Set No	Cyl	Bore Diameter		Ring Size	
					Inch	MM	Comp	Oil
173	80-88	(2.8L) Chevrolet (Deep Oil Ring Groove)	P3830	6	3.504	89.00	6 - 1.50	6 - 4.75
173	81-84	(2.8L) Buick, Oldsmobile, Pontiac (Deep Oil Ring Groove)	C3830				6 - 2.00	
173	85-89	(2.8L) Buick, Cadillac, Chevrolet, Oldsmobile, Pontiac (W/Cast Iron Cyl. Heads) (Shallow Oil Ring Groove)	P3849 C3849	6	3.504	89.00	6 - 1.50 6 - 2.00	6 - 4.75
173	87-89	(2.8L) Buick, Chevrolet, Oldsmobile, Pontiac (W/Aluminum Cyl. Heads)	P3860 C3860	6	3.504	89.00	6 - 1.50 6 - 1.50	6 - 4.00
181	97-00	(3.0L) Cadillac Catera R	P3943 C3943	6	3.386	86.00	6 - 1.50 6 - 1.50	6 - 3.00
181	82-88	(3.0L) Buick, Chevrolet, Oldsmobile, Pontiac	P3814 C3814	6	3.800	96.50	6 - 5/64 6 - 5/64	6 - 3/16
181	69-74	(3.0L) Chevrolet (Marine)	P3819 C3819	4	4.000	101.60	4 - 5/64 4 - 5/64	4 - 3/16
183	99-05	(3.0L) Cadillac Catera (24V) R	S3952⁺	6	3.386	86.00	6 - 1.20 6 - 1.50	6 - 3.00
183	00-06	(3.0L) Saturn L300 (24V) R						
183	00-02	(3.0L) Saturn LS2 (24V) R						
183	00-06	(3.0L) Saturn LW300 (24V) R						
183	00-03	(3.0L) Saturn Vue (24V) R						
189	96-05	(3.1L) Chevrolet K, M	C3920⁺	6	3.504	89.00	6 - 1.20 6 - 1.50	6 - 3.00
189	99-03	(3.1L) Chevrolet (Shallow Oil Ring Groove) J	C3921⁺	6	3.504	89.00	6 - 1.20 6 - 1.50	6 - 3.00
189	88-95	(3.1L) Chevrolet	P3860 C3860	6	3.504	89.00	6 - 1.50 6 - 1.50	6 - 4.00
189	88-92	(3.0L) Pontiac						
194	62-67	(3.2L) Chevrolet	P2234 C2234	6	3.563	90.50	6 - 5/64 6 - 5/64	6 - 3/16
195	61-63	(3.2L) Pontiac	P2237 C2237	4	4.063	103.19	4 - 5/64 4 - 5/64	4 - 3/16
196	78-79	(3.2L) Buick, Chevrolet	P2224 C2224	6	3.500	88.90	6 - 5/64 6 - 5/64	6 - 3/16
197	03-04	(3.2L) Buick, Cadillac CTS Vin: N	S3963^{+N}	6	3.445	87.50	6 - 1.20 6 - 1.50	6 - 2.50
198	62-63	(3.2L) Buick	P2275 C2275	6	3.625	92.10	6 - 5/64 6 - 5/64	6 - 3/16
200	78-79	(3.3L) Chevrolet	P2224 C2224	6	3.500	88.90	6 - 5/64 6 - 5/64	6 - 3/16
204	89-93	(3.3L) Buick	P3867 C3867	6	3.701	94.00	6 - 1.50 6 - 1.50	6 - 3.00
206	34-36	(3.4L) Chevrolet	P2114	6	3.312	84.12	6 - 1/8 6 - 1/8	6 - 3/16
207	96-05	(3.4L) Chevrolet (3mm Oil Groove) E, X	C3923⁺	6	3.622	92.00	6 - 1.20 6 - 1.50	6 - 3.00
207	96-08	(3.4L) Chevrolet (4mm Oil Groove) E, F, X	S3944⁺	6	3.622	92.00	6 - 1.20 6 - 1.50	6 - 4.00
207	91-97	(3.4L) Chevrolet X	P3868 C3868	6	3.622	92.00	6 - 1.50 6 - 1.50	6 - 4.00
207	91-93	(3.4L) Buick X						
213	32-34	(3.5L) Oldsmobile	P2114	6	3.312	84.12	6 - 1/8 6 - 1/8	6 - 3/16
214	99-00	(3.5L) Oldsmobile H	C3934⁺	6	3.524	89.50	6 - 1.20 6 - 1.50	6 - 2.50
214	04-08	(3.5L) LZ43.5N Vin: K, N	S3969^{+N}	6	3.898	99.00	6 - 1.20 6 - 1.50	6 - 2.50
215	61-63	(3.5L) Buick, Oldsmobile, Pontiac	P2291 C2291	8	3.500	88.90	8 - 5/64 8 - 5/64	8 - 3/16

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone

GENERAL MOTORS

Cubic Inch	Year	Application	Set No	Cyl	Bore Diameter		Ring Size		
					Inch	MM	Comp	Oil	
215	64-65	(3.5L) Pontiac	P2276	6	3.750	95.25	6 - 5/64	6 - 3/16	
			C2276				6 - 5/64		
216	37-53	(3.5L) Chevrolet	P2115	6	3.500	88.90	6 - 1/8	6 - 3/16	
			C2115				6 - 1/8		
220	07-10	(3.6L) GMC, Pontiac, Saturn 7	S3962 ^{+N}	6	3.701	94.00	6 - 1.20	6 - 2.50	
220	09-10	(3.6L) Chevrolet 7					6 - 1.50		
220	04-08	(3.6L) Buick, Cadillac 7							
225	64-67	(3.7L) Buick, Oldsmobile, Pontiac	P2276	6	3.750	95.25	6 - 5/64	6 - 3/16	
			C2276				6 - 5/64		
228	41-48	(3.8L) Oldsmobile	P2213	6	3.500	88.90	6 - 3/32	6 - 3/16	
			C2213				6 - 3/32		
229	80-84	(3.8L) Chevrolet	P3820	6	3.736	94.89	6 - 5/64	6 - 3/16	
229	80-81	(3.8L) Pontiac	C3820				6 - 5/64		
230	63-70	(3.8L) Chevrolet	P2240	6	3.875	98.40	6 - 5/64	6 - 3/16	
			C2240				6 - 5/64		
231	80-81	(3.8L) Chevrolet (Turbo)	C3839 ⁺	6	3.800	96.50	6 - 5/64	6 - 3/16	
	231	80-85					(3.8L) Oldsmobile (Turbo)		6 - 5/64
	231	78-89					(3.8L) Buick (Turbo)		
231	93-95	(3.8L) Buick, GMC	C3905 ⁺	6	3.800	96.50	6 - 1.20	6 - 3.00	
							6 - 1.50		
231	95-09	(3.8L) Chevrolet K, 1, 2, 4	C3935 ⁺	6	3.800	96.50	6 - 1.20	6 - 2.00	
							6 - 1.50		
231	74-87	(3.8L) Buick, Chevrolet, Oldsmobile (Non-Turbo)	P3814	6	3.800	96.50	6 - 5/64	6 - 3/16	
	231	75-85	(3.8L) Pontiac (Non-Turbo)				C3814		6 - 5/64
231	87-92	(3.8L) Buick	P3863	6	3.800	96.50	6 - 1.50	6 - 3.00	
			C3863				6 - 1.50		
235	41-49	(3.9L) Chevrolet	P2116	6	3.563	90.50	6 - 1/8	6 - 3/16	
			C2116				6 - 1/8		
235	50-53	(3.9L) Chevrolet (Cast Iron Piston)	P2117	6	3.563	90.50	6 - 3/32	6 - 3/16	
			C2117				6 - 1/8		
235	53-62	(3.9L) Chevrolet (Aluminum Piston)	P2118	6	3.563	90.50	6 - 3/32	6 - 3/16	
235	41-52	(3.9L) Pontiac (Aluminum Piston)	C2118				6 - 3/32		
238	40-50	(3.9L) Buick	P2266	8	3.094	78.58	8 - 3/32	8 - 3/16	
							8 - 3/32		
238	04-08	(3.9L) LZG, LZE Vin: R, W, 1, 3	S3969 ^{+N}	6	3.898	99.00	6 - 1.20	6 - 2.50	
							6 - 1.50		
239	53-54	(3.9L) Pontiac	P2234	6	3.563	90.50	6 - 5/64	6 - 3/16	
			C2234				6 - 5/64		
244	96-99	(4.0L) Oldsmobile Aurora C	C3936 ⁺	8	3.425	87.00	8 - 1.20	8 - 3.00	
							8 - 1.50		
244	94-95	(4.0L) Oldsmobile Aurora	P3904	6	3.425	87.00	6 - 1.50	6 - 3.00	
			C3904				6 - 1.50		
248	37-49	Deluxe Eight, Eight	P2235	8	3.250	82.55	8 - 3/32	8 - 3/16	
							8 - 3/32		
248	37-52	(4.1L) Buick	P2267	8	3.437	87.30	8 - 3/32	8 - 3/16	
			C2267				8 - 3/32		
250	66-84	(4.1L) Chevrolet (With 5/64 Comp. Rings)	P2240	6	3.875	98.40	6 - 5/64	6 - 3/16	
	250	68-76	(4.1L) Pontiac (With 5/64 Comp. Rings)				C2240		6 - 5/64
	250	71-76	(4.1L) Buick, Oldsmobile (With 5/64 Comp. Rings)						
250	66-70	(4.1L) Chevrolet, Oldsmobile (With 1/16 Comp. Rings)	P2243	6	3.875	98.40	6 - 1/16	6 - 3/16	
			C2243				6 - 1/16		
250	1970	(4.1L) Pontiac (With 1/16 Comp. Rings)							
250	68-70	(4.1L) Buick (With 1/16 Comp. Rings)							

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone

GENERAL MOTORS

Cubic Inch	Year	Application	Set No	Cyl	Bore Diameter		Ring Size	
					Inch	MM	Comp	Oil
252	82-88	(4.1L) Cadillac Aluminum Block (Shallow Oil Ring Groove) 250	P3834 C3834	8	3.465	88.00	8 - 5/64 8 - 5/64	8 - 5/32
252	80-84	(4.1L) Buick, Pontiac	P3824	6	3.965	100.71	6 - 5/64	6 - 3/16
252	80-87	(4.1L) Cadillac	C3824				6 - 5/64	
252	81-84	(4.1L) Oldsmobile						
257	39-48	(4.3L) Oldsmobile	P2217 C2217	8	3.250	82.55	8 - 3/32 8 - 3/32	8 - 3/16 8 - 3/16
260	75-79	(4.3L) Buick, Pontiac	P2291	8	3.500	88.90	8 - 5/64	8 - 3/16
260	75-82	(4.3L) Oldsmobile	C2291				8 - 5/64	
261	54-62	(4.3L) Chevrolet	P2813 C2813	6	3.750	95.25	6 - 3/32 6 - 3/32	6 - 3/16
262	75-76	(4.3L) Chevrolet	P3815 C3815	8	3.671	93.22	8 - 5/64 8 - 5/64	8 - 3/16
262	96-97	(4.3L) Chevrolet Vortec W, X	C3914	6	4.000	101.60	6 - 1.50 6 - 1.50	6 - 3.00
262	85-93	(4.3L) Chevrolet N, Z	P3850 C3850	6	4.000	101.60	6 - 2.00 6 - 2.00	6 - 4.75
262	90-95	(4.3L) Chevrolet	P3883	6	4.000	101.60	6 - 2.00	6 - 4.00
262	82-85	(4.3L) Buick					6 - 1.50	
262	88-95	(4.3L) Chevrolet Z	P3913 C3913	6	4.000	101.60	6 - 2.00 6 - 2.00	6 - 4.75
263	50-53	(4.3L) Buick	P3108 C3108	8	3.187	80.95	8 - 3/32 8 - 3/32	8 - 3/16 8 - 3/16
263	82-85	(4.3L) Chevrolet, Oldsmobile, Pontiac (Diesel)	C3838 +	6	4.057	103.05	6 - 2.00	6 - 4.75
263	1985	(4.3L) Cadillac (Diesel)					6 - 2.00	
264	54-55	(4.3L) Buick	P2145 C2145	8	3.625	92.10	8 - 5/64 8 - 5/64	8 - 3/16
265	94-96	(4.3L) Chevrolet (Shallow Oil Ring Groove) W	P3886 C3886	8	3.736	94.89	8 - 2.00 8 - 2.00	8 - 4.75
265	55-57	(4.3L) Chevrolet	P2119 C2119	8	3.750	95.25	8 - 5/64 8 - 5/64	8 - 3/16
265	80-82	(4.3L) Buick, Oldsmobile, Pontiac (Shallow Oil Ring Groove)	P3832 C3832	8	3.750	95.25	8 - 5/64	8 - 3/16
265	80-82	(4.3L) Pontiac (Shallow Oil Ring Groove)					8 - 5/64	
267	79-82	(4.4L) Chevrolet	P2291	8	3.500	88.90	8 - 5/64	8 - 3/16
267	81-82	(4.4L) Oldsmobile, Pontiac	C2291				8 - 5/64	
268	50-54	(4.4L) Pontiac	P2236 C2236	8	3.375	85.70	8 - 3/32 8 - 3/32	8 - 3/16
274	87-92	(4.5L) Cadillac Aluminum Block	P3862 C3862	8	3.622	92.00	8 - 1.50 8 - 1.50	8 - 3.00
281	96-99	(4.6L) Cadillac Y, 9	C3937 +	8	3.661	93.00	8 - 1.20 8 - 1.50	8 - 3.00
281	00-05	(4.6L) Cadillac Y, 9	C3938 +	8	3.661	93.00	8 - 1.20 8 - 1.50	8 - 2.50
281	93-95	(4.6L) Cadillac	P3891 C3891	8	3.661	93.00	8 - 1.50 8 - 1.50	8 - 3.00
283	57-67	(4.6L) Chevrolet	P2221 C2221	8	3.875	98.40	8 - 5/64 8 - 5/64	8 - 3/16
287	1955	(4.7L) Pontiac	P2119 C2119	8	3.750	95.25	8 - 5/64 8 - 5/64	8 - 3/16
292	63-89	(4.8L) Chevrolet	P2241 C2241	6	3.875	98.40	6 - 3/32 6 - 3/32	6 - 3/16
294	99-11	(4.8L) Chevrolet (Shallow Top Groove) A, C, V	P3941 C3941	8	3.780	96.00	8 - 1.50 8 - 1.50	8 - 3.00

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone

GENERAL MOTORS

Cubic Inch	Year	Application	Set No	Cyl	Bore Diameter		Ring Size	
					Inch	MM	Comp	Oil
300	64-67	(4.9L) Buick	P2119 C2119	8	3.750	95.25	8 - 5/64	8 - 3/16
301	1980	(4.9L) Buick, Chevrolet (Turbo)	C3840 +	8	4.000	101.60	8 - 5/64	8 - 3/16
301	80-81	(4.9L) Pontiac (Turbo)					8 - 5/64	
301	77-80	(4.9L) Buick, Oldsmobile, Pontiac	P2271 C2271	8	4.000	101.60	8 - 5/64	8 - 3/16
301	80-81	(4.9L) Buick, Pontiac Non-Turbo (O.E. Piston) (Shallow Oil Ring Groove)	P3823 C3823	8	4.000	101.60	8 - 5/64	8 - 3/16
302	67-70	(5.0L) Chevrolet	P2271 C2271	8	4.000	101.60	8 - 5/64	8 - 3/16
303	49-53	(5.0L) Oldsmobile	P2119 C2119	8	3.750	95.25	8 - 5/64	8 - 3/16
305	76-93	(5.0L) Chevrolet	P3817 C3817	8	3.736	94.89	8 - 5/64	8 - 3/16
305	77-92	(5.0L) Oldsmobile, Pontiac					8 - 5/64	
305	77-81	(5.0L) Buick						
305	93-02	(5.0L) Chevrolet (Shallow Oil Groove) M	P3886 C3886	8	3.736	94.89	8 - 2.00	8 - 4.75
307	80-90	(5.0L) Buick, Cadillac, Oldsmobile, Pontiac	P2158 C2158	8	3.800	96.50	8 - 5/64	8 - 3/16
307	68-73	(5.0L) Chevrolet, Pontiac	P2221 C2221	8	3.875	98.40	8 - 5/64	8 - 3/16
316	1956	(5.2L) Pontiac	P3158 C3158	8	3.937	100.00	8 - 5/64	8 - 3/16
320	40-52	(5.3L) Buick	P2267 C2267	8	3.437	87.30	8 - 3/32	8 - 3/16
322	56-60	(5.3L) Chevrolet	P2271 C2271	8	4.000	101.60	8 - 5/64	8 - 3/16
322	53-56	(5.3L) Buick 40, 50, 60, 70 Series					8 - 5/64	
324	54-56	(5.3L) Oldsmobile, Pontiac	P2221 C2221	8	3.875	98.40	8 - 5/64	8 - 3/16
326	64-67	(5.3L) Pontiac	P2146 C2146	8	3.720	94.50	8 - 5/64	8 - 3/16
326	1963	(5.3L) Pontiac	P2149 C2149	8	3.780	96.00	8 - 5/64	8 - 3/16
327	62-69	(5.4L) Chevrolet	P2271 C2271	8	4.000	101.60	8 - 5/64	8 - 3/16
330	64-67	(5.4L) Oldsmobile	P3158 C3158	8	3.937	100.00	8 - 5/64	8 - 3/16
331	49-55	(5.4L) Cadillac	P2339 C2339	8	3.813	96.85	8 - 5/64	8 - 3/16
340	66-67	(5.6L) Buick	P2119 C2119	8	3.750	95.25	8 - 5/64	8 - 3/16
346	46-48	(5.7L) Cadillac	P2291 C2291	8	3.500	88.90	8 - 5/64	8 - 3/16
347	1957	(5.7L) Pontiac	P3158 C3158	8	3.937	100.00	8 - 5/64	8 - 3/16
348	58-65	(5.7L) Chevrolet	P2187 C2187	8	4.125	104.78	8 - 5/64	8 - 3/16
350	68-81	(5.7L) Buick (Corporate eng.) X(76-80) H(76-77) J(76-77)	P2158 C2158	8	3.800	96.50	8 - 5/64	8 - 3/16
350	68-77	(5.7L) Pontiac	P2221 C2221	8	3.875	98.40	8 - 5/64	8 - 3/16
350	97-04	(5.7L) Chevrolet Corvette, Pontiac Firebird G, S	P3939 C3939	8	3.898	99.00	8 - 1.50	8 - 3.00
350	97-04	(5.7L) Chevrolet Camaro G					8 - 1.50	

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone

GENERAL MOTORS

Cubic Inch	Year	Application	Set No	Cyl	Bore Diameter		Ring Size	
					Inch	MM	Comp	Oil
350	86-88	(5.7L) Chevrolet Trucks (Shallow Oil Ring Groove) K	C3853	8	4.000	101.60	8 - 5/64 8 - 5/64	8 - 3/16
350	67-85	(5.7L) Chevrolet L(76-82) G(77) H(78) V(76)	P2271	8	4.000	101.60	8 - 5/64	8 - 3/16
350	77-79	(5.7L) Buick, Oldsmobile, Pontiac L(76-82) G(77) H(78) V(76)	C2271				8 - 5/64	
350	86-89	(5.7L) Chevrolet (Shallow Oil Ring Groove) K	P3823 C3823	8	4.000	101.60	8 - 5/64 8 - 5/64	8 - 3/16
350	89-92	(5.7L) Chevrolet MAHLE piston deep groove P, 7, 8	P3866 C3866	8	4.000	101.60	8 - 2.00 8 - 1.50	8 - 4.00
350	90-95	(5.7L) Chevrolet (Shallow Oil Ring Groove) P, R, 5, 7, 8	P3876 C3876	8	4.000	101.60	8 - 2.00 8 - 1.50	8 - 4.00
350	96-02	(5.7L) Chevrolet Vortec (Shallow Oil Ring Groove) R	P3890 C3890	8	4.000	101.60	8 - 1.50 8 - 1.50	8 - 3.00
350	80-85	(5.7L) Pontiac (Diesel) N	C3837 +	8	4.057	103.05	8 - 5/64	8 - 3/16
350	78-85	(5.7L) Buick, Cadillac, Chevrolet (Diesel) N					8 - 5/64	
350	78-86	(5.7L) Oldsmobile (Diesel) N						
350	76-80	(5.7L) Buick, Cadillac, Pontiac R	P2245	8	4.057	103.05	8 - 5/64	8 - 3/16
350	68-80	(5.7L) Oldsmobile R	C2245				8 - 5/64	
350	68-80	(5.7L) Oldsmobile, Pontiac R						
364	57-61	(6.0L) Buick	P2187 C2187	8	4.125	104.78	8 - 5/64 8 - 5/64	8 - 3/16
365	56-57	(6.0L) Cadillac	P2271 C2271	8	4.000	101.60	8 - 5/64 8 - 5/64	8 - 3/16
366	66-90	(6.0L) Chevrolet Medium Duty	P3770 C3770	8	3.937	100.00	8 - 3/32 8 - 5/64	8 - 3/16
366	66-85	(6.0L) Chevrolet Heavy Duty (4-Ring)	P3771 C3771	8	3.937	100.00	8 - 3/32 8 - 5/64 8 - 5/64	8 - 3/16
366	91-97	(6.0L) Chevrolet (Shallow Oil Ring Groove)	P3879 C3879	8	3.937	100.00	8 - 3/32 16 - 5/64	8 - 3/16
368	80-84	(6.0L) Cadillac	P3822 C3822	8	3.800	96.50	8 - 5/64 8 - 5/64	8 - 3/16
370	1958	(6.1L) Pontiac	P2135 C2135	8	4.063	103.19	8 - 5/64 8 - 5/64	8 - 3/16
371	57-60	(6.1L) Oldsmobile	P3150 C3150	8	4.000	101.60	8 - 5/64 8 - 3/32	8 - 3/16
389	59-66	(6.4L) Pontiac	P2135 C2135	8	4.063	103.19	8 - 5/64 8 - 5/64	8 - 3/16
390	58-63	(6.4L) Cadillac	P2271 C2271	8	4.000	101.60	8 - 5/64 8 - 5/64	8 - 3/16
394	59-64	(6.6L) Oldsmobile	P2222 C2222	8	4.125	104.78	8 - 5/64 8 - 3/32	8 - 3/16
396	65-69	(6.6L) Chevrolet	P2136 C2136	8	4.094	104.00	8 - 5/64 8 - 5/64	8 - 3/16
396	70-76	(6.6L) Chevrolet	P2187 C2187	8	4.125	104.78	8 - 5/64 8 - 5/64	8 - 3/16
400	68-69	(6.6L) Oldsmobile	P2246 C2246	8	3.870	98.30	8 - 5/64 8 - 5/64	8 - 3/16
400	65-67	(6.6L) Oldsmobile	P2271 C2271	8	4.000	101.60	8 - 5/64 8 - 5/64	8 - 3/16
400	67-69	(6.6L) Buick	P2277 C2277	8	4.040	102.61	8 - 5/64 8 - 5/64	8 - 3/16
400	67-79	(6.6L) Buick, Oldsmobile, Pontiac	P2137 C2137	8	4.120	104.64	8 - 5/64 8 - 5/64	8 - 3/16

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone

GENERAL MOTORS

Cubic Inch	Year	Application	Set No	Cyl	Bore Diameter		Ring Size	
					Inch	MM	Comp	Oil
400	70-80	(6.6L) Chevrolet	P2187 C2187	8	4.125	104.78	8 - 5/64 8 - 5/64	8 - 3/16
400	1966	(6.6L) Buick	P2377 C2377	8	4.188	106.36	8 - 5/64 8 - 5/64	8 - 3/16
401	59-66	(6.6L) Buick	P2377 C2377	8	4.188	106.36	8 - 5/64 8 - 5/64	8 - 3/16
402	70-72	(6.6L) Chevrolet	P2187 C2187	8	4.125	104.78	8 - 5/64 8 - 5/64	8 - 3/16
403	77-79	(6.6L) Buick, Oldsmobile, Pontiac	P3818 C3818	8	4.351	110.52	8 - 5/64 8 - 5/64	8 - 3/16
409	62-65	(6.7L) Chevrolet	P2379 C2379	8	4.313	109.54	8 - 5/64 8 - 5/64	8 - 3/16
421	63-66	(6.9L) Pontiac	P2136 C2136	8	4.094	104.00	8 - 5/64 8 - 5/64	8 - 3/16
425	77-79	(7.0L) Cadillac	P3821 C3821	8	4.082	103.70	8 - 5/64 8 - 5/64	8 - 3/16
425	65-67	(7.0L) Oldsmobile	P2187 C2187	8	4.125	104.78	8 - 5/64 8 - 5/64	8 - 3/16
425	63-66	(7.0L) Buick	P2379 C2379	8	4.313	109.54	8 - 5/64 8 - 5/64	8 - 3/16
427	66-76	(7.0L) Chevrolet	P2378 C2378	8	4.250	107.95	8 - 5/64 8 - 5/64	8 - 3/16
427	68-88	(7.0L) Chevrolet 4-Ring Marine Engine	P3810 C3810	8	4.250	107.95	8 - 3/32 8 - 5/64 8 - 5/64	8 - 3/16
428	67-69	(7.0L) Pontiac	P2137 C2137	8	4.120	104.64	8 - 5/64 8 - 5/64	8 - 3/16
429	64-65	(7.0L) Cadillac	P2340 C2340	8	4.129	104.87	8 - 1/16 8 - 1/16	8 - 1/8
429	66-67	(7.0L) Cadillac	P2341 C2341	8	4.129	104.87	8 - 1/16 8 - 1/16	8 - 3/16
430	67-69	(7.0L) Buick	P2377 C2377	8	4.188	106.36	8 - 5/64 8 - 5/64	8 - 3/16
454	71-90	(7.4L) Chevrolet L.D.	P2378 C2378	8	4.250	107.95	8 - 5/64 8 - 5/64	8 - 3/16
454	70-88	(7.4L) Chevrolet M.D.	P3810 C3810	8	4.250	107.95	8 - 3/32 8 - 5/64 8 - 5/64	8 - 3/16
454	91-00	(7.4L) Chevrolet L.D. (Shallow Oil Ring Groove)	P3875 C3875	8	4.250	107.95	8 - 5/64 8 - 5/64	8 - 3/16
455	68-76	(7.5L) Oldsmobile	P2187 C2187	8	4.125	104.78	8 - 5/64 8 - 5/64	8 - 3/16
455	70-76	(7.5L) Pontiac	P2138 C2138	8	4.151	105.43	8 - 5/64 8 - 1/16	8 - 3/16
455	70-76	(7.5L) Buick	P2379 C2379	8	4.313	109.54	8 - 5/64 8 - 5/64	8 - 3/16
472	68-74	(7.7L) Cadillac	P2342 C2342	8	4.300	109.22	8 - 5/64 8 - 5/64	8 - 3/16
500	70-76	(8.2L) Cadillac	P2342 C2342	8	4.300	109.22	8 - 5/64 8 - 5/64	8 - 3/16

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone