

HERCULES

Cubic Inch	Year	Application	Set No	Cyl	Bore Diameter		Ring Size	
					Inch	MM	Comp	Oil
		ZXB (Late Model)	P2653	4	2.625	66.68	4 - 3/32 4 - 3/32	4 - 3/16
		IXA, NXA	P2834	4	3.000	76.20	4 - 1/8 4 - 1/8	4 - 3/16
		IXB (Early)	P2672	4	3.250	82.55	4 - 1/8 4 - 1/8	4 - 3/16
		QXD (Sleeved Engine)	P2417	6	3.437	87.30	6 - 1/8 6 - 1/8 6 - 1/8	6 - 3/16
		QXD, QXLD, QXLDM (Marine)	P2631 C2631	6	3.437	87.30	6 - 3/32 6 - 1/8	6 - 3/16
		QXD5M (Marine)	P2877 C2877	6	3.437	87.30	6 - 3/32 6 - 3/32	6 - 3/16
		JXE, JXG	P2480 C2480	6	3.500	88.90	6 - 1/8 6 - 1/8 6 - 1/8	6 - 3/16
		OOA, JX4E (Diesel)	P2746	4	3.500	88.90	4 - 1/8 4 - 1/8 4 - 1/8	4 - 3/16
		JXC	P2418	6	3.750	95.25	6 - 1/8 6 - 1/8 6 - 1/8	6 - 3/16
		JX4C	P2606 C2606	4	3.750	95.25	4 - 1/8 4 - 1/8 4 - 1/8	4 - 3/16

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone