

WILLYS (JEEP)

Cubic Inch	Year	Application	Set No	Cyl	Bore Diameter		Ring Size	
					Inch	MM	Comp	Oil
134	40-74	(2.2L)	P2161 C2161	4	3.125	79.37	4 - 3/32 4 - 3/32	4 - 3/16
150	83-92	(2.5L)	P2238 C2238	4	3.875	98.40	4 - 5/64 4 - 5/64	4 - 3/16
151	80-81	(2.5L)	P3835 C3835	4	4.000	101.60	4 - 5/64 4 - 5/64	4 - 3/16
151	82-84	(2.5L)	P3836 C3836	4	4.000	101.60	4 - 1/16 4 - 5/64	4 - 3/16
151	82-93	(2.5L)	P3884	4	4.000	101.60	4 - 1.60 4 - 2.00	4 - 4.75
161	50-62	(2.6L)	P2199 C2199	6	3.125	79.37	6 - 3/32 6 - 3/32	6 - 3/16
173	84-86	(2.8L) (Shallow Oil Ring Groove)	P3849 C3849	6	3.504	89.00	6 - 1.50 6 - 2.00	6 - 4.75
225	66-73	(3.7L)	P2276 C2276	6	3.750	95.25	6 - 5/64 6 - 5/64	6 - 3/16
226	54-65	(3.7L) (Continental)	P2315 C2315	6	3.312	84.12	6 - 3/32 6 - 3/32	6 - 5/32 6 - 5/32
230	62-68	(3.8L) (OHC)	P2163 C2163	6	3.344	84.93	6 - 5/64 6 - 5/64	6 - 3/16
232	65-83	(3.8L)	P2276 C2276	6	3.750	95.25	6 - 5/64 6 - 5/64	6 - 3/16
258	71-86	(4.2L)	P2276 C2276	6	3.750	95.25	6 - 5/64 6 - 5/64	6 - 3/16
304	71-81	(5.0L)	P2119 C2119	8	3.750	95.25	8 - 5/64 8 - 5/64	8 - 3/16
327	65-68	(5.4L)	P2271 C2271	8	4.000	101.60	8 - 5/64 8 - 5/64	8 - 3/16
350	68-73	(5.7L)	P2158 C2158	8	3.800	96.50	8 - 5/64 8 - 5/64	8 - 3/16
360	71-92	(5.9L)	P2292 C2292	8	4.080	103.60	8 - 5/64 8 - 5/64	8 - 3/16
401	74-78	(6.6L)	P2293 C2293	8	4.165	105.79	8 - 5/64 8 - 5/64	8 - 3/16

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone