

CHRYSLER

Cubic Inch	Year	Application	Set No	Cyl	Bore Diameter		Ring Size	
					Inch	MM	Comp	Oil
85	79-85	(1.4L) Dodge Colt, Plymouth Champ (Mits. eng.) G12B, J	P1417 C1417	4	2.913	74.00	4 - 1.50 4 - 1.50	4 - 4.00
91	70-73	(1.5L) Plymouth Cricket	P1332 C1332	4	3.391	86.10	4 - 5/64 4 - 5/64	4 - 5/32
92	91-96	(1.5L) Dodge/Plymouth Colt, Eagle Summit 12V 4G15, Q	C1778 ⁺	4	2.972	75.50	4 - 1.20 4 - 1.50	4 - 3.00
92	85-90	(1.5L) Dodge/Plymouth Colt (Mits. eng.) G15B, Q	P1602 C1602	4	2.972	75.50	4 - 1.50 4 - 1.50	4 - 4.00
97	83-88	(1.6L) Dodge Omni, Plymouth Horizon (Peugeot eng.)	P1587 C1587	4	3.174	80.62	4 - 1.75 4 - 2.00	4 - 4.00
98	71-84	(1.6L) Dodge, Plymouth (Mits. eng.) G32B, K, Z	P1298 C1298	4	3.028	76.90	4 - 2.00 4 - 2.00	4 - 4.00
98	85-88	(1.6L) Dodge/Plymouth Colt (Mits. eng.) G32B	P1604 C1604	4	3.028	76.90	4 - 1.50 4 - 1.50	4 - 4.00
98	89-93	(1.6L) Dodge Colt, Eagle Summit (Mits. eng.) G61B, K	C1724 ⁺	4	3.240	82.30	4 - 1.20 4 - 1.50	4 - 3.00
105	78-83	(1.7L) Dodge Omni, Plymouth (VW eng.) E82	P1429 C1429	4	3.130	79.50	4 - 1.75 4 - 2.00	4 - 4.00
107	89-94	(1.8L) Laser G37B, P	P1645 C1645	4	3.173	80.60	4 - 1.50 4 - 1.50	4 - 4.00
110	78-88	(1.8L) Dodge/Plymouth Colt (Mits. eng.) G62B	P1527 C1527	4	3.173	80.60	4 - 2.00 4 - 2.00	4 - 4.00
110	06-09	(1.8L) Dodge Caliber GEMA 1.8	S5410 ⁺	4	3.386	86.00	4 - 1.20 4 - 1.20	4 - 2.00
112	92-94	(1.8L) Dodge/Plymouth Colt/Colt Vista	C3892 ⁺	4	3.189	81.00	4 - 1.20 4 - 1.20	4 - 2.80
121	95-00	(2.0L) Dodge Stratus C, F	P3896 ⁺	4	3.445	87.50	4 - 1.20	4 - 3.00
121	95-05	(2.0L) Dodge Neon, L4 C, F	C3896 ⁺				4 - 1.20	
122	72-82	(2.0L) Dodge, Plymouth (Mits. eng.) G52B, U	P1331 C1331	4	3.307	84.00	4 - 2.00 4 - 2.00	4 - 4.00
122	89-92	(2.0L) Eagle (N.A. & Turbo) G63B	C1775 ⁺	4	3.346	85.00	4 - 1.20	4 - 3.00
122	90-91	(2.0L) Eagle (N.A. & Turbo) G63B					4 - 1.50	
122	95-98	(2.0L) 4G63	C1951 ⁺	4	3.346	85.00	4 - 1.20 4 - 1.50	4 - 2.80
122	83-86	(2.0L) Dodge, Plymouth (Mits. eng.) G63B, A	P1528 C1528	4	3.346	85.00	4 - 2.00 4 - 2.00	4 - 4.00
122	07-15	(2.0L) Jeep Patriot GEMA 2.0	S5410 ⁺	4	3.386	86.00	4 - 1.20	4 - 2.00
122	06-12	(2.0L) Dodge Caliber GEMA 2.0					4 - 1.20	
122	07-15	(2.0L) Jeep Compass GEMA 2.0						
135	85-93	(2.2L) Dodge/Plymouth (Turbo)	C1714 ⁺	4	3.445	87.50	4 - 1.50	4 - 4.00
135	82-93	(2.2L) Chrysler (Turbo)					4 - 1.50	
135	92-97	(2.2L) Chrysler (Turbo), 16V	C3893 ⁺	4	3.445	87.50	4 - 1.50 4 - 1.50	4 - 3.00
135	81-89	(2.2L) Plymouth Reliant	P1486	4	3.445	87.50	4 - 1.50	4 - 4.00
135	81-85	(2.2L) Dodge Aries	C1486				4 - 1.50	
135	84-88	(2.2L) Chrysler LeBaron E62						
135	82-95	(2.2L) Dodge (Shallow Oil Ring Groove)	P1830	4	3.445	87.50	4 - 1.50	4 - 4.00
135	85-95	(2.2L) Chrysler (Shallow Oil Ring Groove)	C1830				4 - 1.50	
143	83-86	(2.3L) Dodge D-50 Pickup, Plymouth Ram 50 (Mits. eng.) (Diesel) 4D55, D	C1530 ⁺	4	3.587	91.10	4 - 2.50 ^{HK} 4 - 2.00 ^{HK}	4 - 4.00
144	07-15	(2.4L) Jeep Patriot GEMA 2.4	S5335 ⁺	4	3.465	88.00	4 - 1.20	4 - 2.00
144	07-10	(2.4L) Chrysler Sebring GEMA 2.4					4 - 1.20	
144	07-15	(2.4L) Dodge Avenger GEMA 2.4						
144	09-15	(2.4L) Dodge Journey GEMA 2.4						

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone

CHRYSLER

Cubic Inch	Year	Application	Set No	Cyl	Bore Diameter		Ring Size	
					Inch	MM	Comp	Oil
144	06-12	(2.4L) Dodge Caliber GEMA 2.4						
144	07-15	(2.4L) Jeep Compass GEMA 2.4						
144	11-14	(2.4L) Chrysler 200 GEMA 2.4						
146	01-06	(2.4L) Dodge Stratus (Mits. eng.) 4G64	C1883 ⁺	4	3.406	86.50	4 - 1.20	4 - 2.80
146	93-96	(2.4L) Dodge Colt Vista, Eagle Summit (Mits. eng.) 4G64					4 - 1.50	
146	01-08	(2.4L) Chrysler Sebring (Mits. eng.) 4G64						
146	90-93	(2.4L) Dodge RAM 50 (Mits. eng.) 4G64	P1652	4	3.406	86.50	4 - 1.50	4 - 4.00
146	1992	(2.4L) Eagle Summit (Mits. eng.) G64B	C1652				4 - 1.50	
146	90-92	(2.4L) Dodge Colt Vista (Mits. eng.) 4G64						
146	05-06	(2.4L) Dodge SRT-4 EDT 2.4, E	S3959 ⁺	4	3.445	87.50	4 - 1.20	4 - 2.50
146	03-06	(2.4L) Dodge Neon EDT 2.4, E					4 - 1.50	
146	03-10	(2.4L) Chrysler PT Cruiser EDT 2.4, E						
146	93-05	(2.4L) Mitsubishi RDS2 4G64	C3968 ⁺	4	3.465	88.00	4 - 1.20	4 - 2.00
							4 - 1.20	
148	98-05	(2.4L) Incl. Turbo B, G, X, 1	C3918 ⁺	4	3.445	87.50	4 - 1.20	4 - 3.00
148	98-01	(2.4L) Dodge Stratus B, G, X, 1					4 - 1.50	
148	98-00	(2.4L) Dodge Caravan B, G, X, 1						
148	03-08	(2.4L) Chrysler PT Cruiser	P3897	4	3.445	87.50	4 - 1.50	4 - 3.00
148	96-97	(2.4L) Chrysler Sebring, Dodge Caravan, Grand Caravan, Plymouth Breeze, Grand Voyager	C3897				4 - 1.50	
148	03-06	(2.4L) Chrysler Sebring, Dodge Stratus						
148	01-04	(2.4L) Dodge Caravan, Plymouth Voyager						
148	95-97	(2.4L) Dodge Stratus, Plymouth Cirrus						
148	2002	(2.4L) Chrysler PT Cruiser, Sebring, Dodge Stratus						
152	95-00	(2.5L) Chrysler Cirrus 6G73	C5004 ⁺	6	3.287	83.50	6 - 1.20	6 - 3.00
152	95-00	(2.5L) Avenger, Cirrus, Sebring, Stratus 6G73					6 - 1.50	
152	98-00	(2.5L) Dodge Dakota 2.5 8V Turbo Diesel (Diesel) VM425	S5317 ^N	4	3.622	92.00	4 - 2.50 ^{FK}	4 - 2.00
							4 - 1.50	
153	86-95	(2.5L) Chrysler (Turbo) (Shallow Oil Ring Groove)	C3885 ⁺	4	3.445	87.50	4 - 1.50	4 - 4.00
							4 - 1.50	
153	94-97	(2.5L) Chrysler (Turbo) (Shallow Oil Ring Groove)	C3922 ⁺	4	3.445	87.50	4 - 1.50	4 - 4.00
							4 - 1.50	
153	86-89	(2.5L) Dodge, Plymouth	P1486 C1486	4	3.445	87.50	4 - 1.50	4 - 4.00
							4 - 1.50	
153	82-93	(2.5L) Eagle Premier (Turbo)	P2238 C2238	4	3.875	98.40	4 - 5/64	4 - 3/16
							4 - 5/64	
153	96-99	(2.5L) Dodge L4	P3926 C3926	4	3.875	98.40	4 - 1.50	4 - 4.00
							4 - 1.50	
155	82-84	(2.6L) Chrysler LeBaron, New Yorker (Mits. eng.) G54B	P1438 C1438	4	3.587	91.10	4 - 2.00	4 - 4.00
							4 - 2.00	
156	77-83	(2.5L) Chrysler, Dodge, Plymouth (Mits. eng.) G54B	P1438 C1438	4	3.587	91.10	4 - 2.00	4 - 4.00
							4 - 2.00	
156	83-89	(2.6L) Chrysler, Dodge, Plymouth (Mits. eng.) G54B	P1529	4	3.587	91.10	4 - 1.50	4 - 4.00
156	1985	(2.6L) Chrysler LeBaron, New Yorker (Mits. eng.) G54B	C1529				4 - 1.50	
167	98-03	(2.7L) 2700 Vin: R, T, U	S3974 ⁺	6	3.386	86.00	6 - 1.50	6 - 3.00
							6 - 1.50	
167	98-05	(2.7L) Chrysler Concorde, Dodge Intrepid	P3925 C3925	6	3.386	86.00	6 - 1.50	6 - 3.00
							6 - 1.50	
170	60-69	(2.8L) Dodge, Plymouth	P2128 C2128	6	3.400	86.36	6 - 5/64	6 - 3/16
							6 - 5/64	
181	91-95	(3.0L) Chrysler (N.A. & Turbo) V (Sell out and reorder C1841 or P1841)	C3878	6	3.587	91.10	6 - 1.20	6 - 3.00
							6 - 1.50	

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone

CHRYSLER

Cubic Inch	Year	Application	Set No	Cyl	Bore Diameter		Ring Size	
					Inch	MM	Comp	Oil
181	87-93	(3.0L) Dodge Dynasty LE, Plymouth Caravan, 12V (Mits. eng.) G72B	P1664 C1664	6	3.587	91.10	6 - 1.50 6 - 1.50	6 - 4.00
182	90-91	(3.0L) Dodge Monaco (Renault eng.)	P1774 ^A C1774 ^A	6	3.661	93.00	6 - 1.75 6 - 1.75	6 - 3.50
197	98-01	(3.2L) Chrysler Concorde, Dodge Intrepid J	C3923 ⁺	6	3.622	92.00	6 - 1.20 6 - 1.50	6 - 3.00
198	70-74	(3.2L) Dodge, Plymouth	P2128 C2128	6	3.400	86.36	6 - 5/64 6 - 5/64	6 - 3/16
201	88-97	(3.3L) Dodge, Plymouth	P3877 C3877	6	3.661	93.00	6 - 1.50 6 - 1.50	6 - 3.00
201	98-05	(3.3L) Chrysler (Shallow Oil Ring Groove) G, R, 3	P3924 C3924	6	3.661	93.00	6 - 1.50 6 - 1.50	6 - 3.00
215	96-10	(3.5L) Chrysler F, G, K, V	C3887 ⁺	6	3.780	96.00	6 - 1.20	6 - 3.00
215	1997	(3.5L) Plymouth Prowler F, G, K, V					6 - 1.50	
215	95-97	(3.5L) Chrysler Concorde, Dodge Intrepid, Chrysler LHS, Eagle Vision F, G, K, V						
215	95-96	(3.5L) Chrysler New Yorker F, G, K, V						
218	42-59	(3.6L) Dodge, Plymouth	P2124 C2124	6	3.250	82.55	6 - 3/32 6 - 3/32	6 - 5/32 6 - 5/32
218	35-40	(3.6L) Dodge	P2130 C2130	6	3.250	82.55	6 - 1/8 6 - 1/8	6 - 5/32 6 - 5/32
225	60-87	(3.7L) Dodge, Plymouth	P2128	6	3.400	86.36	6 - 5/64	6 - 3/16
225	76-85	(3.7L) Chrysler	C2128				6 - 5/64	
228	35-41	(3.8L) Desoto	P2140	6	3.375	85.70	6 - 1/8	6 - 5/32
228	38-41	(3.8L) Chrysler	C2140				6 - 1/8	6 - 5/32
230	42-59	(3.8L) Dodge, Plymouth	P2124 C2124	6	3.250	82.55	6 - 3/32 6 - 3/32	6 - 5/32 6 - 5/32
231	91-02	(3.8L) Dodge, Plymouth L, 6	P3874 C3874	6	3.780	96.00	6 - 1.50 6 - 1.50	6 - 3.00
237	42-51	(3.9L) Desoto	P2142	6	3.437	87.30	6 - 3/32	6 - 5/32
237	42-54	(3.9L) Dodge Canada	C2142				6 - 3/32	6 - 5/32
239	87-91	(3.9L) Dodge, Plymouth	P1620 C1620	6	3.910	99.30	6 - 5/64 6 - 5/64	6 - 3/16
239	92-03	(3.9L) Dodge Truck	P3912 C3912	6	3.910	99.30	6 - 2.00 6 - 2.00	6 - 4.00
241	53-55	(3.9L) Dodge, Plymouth	P2132 C2132	8	3.437	87.30	8 - 5/64 8 - 5/64	8 - 3/16
251	55-68	(4.1L) Dodge Truck	P2134 C2134	6	3.437	87.30	6 - 5/64 6 - 5/64	6 - 3/16
251	49-51	(4.1L) Desoto	P2142	6	3.437	87.30	6 - 3/32	6 - 5/32
251	42-52	(4.1L) Chrysler	C2142				6 - 3/32	6 - 5/32
259	55-56	(4.2L) Dodge	P2186	8	3.563	90.50	8 - 5/64	8 - 3/16
259	1955	(4.1L) Plymouth K	C2186				8 - 5/64	
265	55-68	(4.3L) Dodge Truck	P2134 C2134	6	3.437	87.30	6 - 5/64 6 - 5/64	6 - 3/16
265	51-54	(4.3L) Exc. Canada	P2142	6	3.437	87.30	6 - 3/32	6 - 5/32
265	42-51	(4.3L) Desoto	C2142				6 - 3/32	6 - 5/32
270	55-56	(4.4L) Dodge, Plymouth	P2145 C2145	8	3.625	92.10	8 - 5/64 8 - 5/64	8 - 3/16
273	64-69	(4.5L) Dodge, Plymouth	P2145 C2145	8	3.625	92.10	8 - 5/64 8 - 5/64	8 - 3/16
276	52-54	(4.5L) Desoto	P2145 C2145	8	3.625	92.10	8 - 5/64 8 - 5/64	8 - 3/16

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone

CHRYSLER

Cubic Inch	Year	Application	Set No	Cyl	Bore Diameter		Ring Size	
					Inch	MM	Comp	Oil
277	56-57	(4.5L) Plymouth	P2119 C2119	8	3.750	95.25	8 - 5/64 8 - 5/64	8 - 3/16
287	07-09	(4.7L) Aspen, SUV, Flex Fuel, SOHC Power Tech 4.7	S4000 ^{+N}	8	3.661	93.00	8 - 1.20 8 - 1.50	8 - 2.50
287	99-07	(4.7L) Dodge Truck N	P3927 C3927	8	3.661	93.00	8 - 1.50 8 - 1.50	8 - 3.00
290	55-56	(4.7L) Desoto	P2146 C2146	8	3.720	94.50	8 - 5/64 8 - 5/64	8 - 3/16
301	1955	(4.9L) Chrysler	P2145 C2145	8	3.625	92.10	8 - 5/64 8 - 5/64	8 - 3/16
301	1957	(4.9L) Plymouth	P2127 C2127	8	3.910	99.30	8 - 5/64 8 - 5/64	8 - 3/16
303	54-56	(5.0L) Dodge	P2339 C2339	8	3.813	96.85	8 - 5/64 8 - 5/64	8 - 3/16
315	1956	(5.2L) Dodge	P2145 C2145	8	3.625	92.10	8 - 5/64 8 - 5/64	8 - 3/16
318	60-93	(5.2L) Dodge	P2127	8	3.910	99.30	8 - 5/64	8 - 3/16
318	58-89	(5.2L) Plymouth	C2127				8 - 5/64	
318	75-89	(5.2L) Chrysler						
318	91-03	(5.2L) Dodge Truck (Shallow Oil Ring Groove)	P3911 C3911	8	3.910	99.30	8 - 2.00 8 - 2.00	8 - 4.00
324	42-50	(5.4L) Chrysler C30, C36, IND9, IND12	P2143	8	3.250	82.55	8 - 3/32 8 - 3/32	8 - 5/32 8 - 5/32
325	1957	(5.3L) Desoto	P2148	8	3.688	93.67	8 - 5/64	8 - 3/16
325	57-58	(5.3L) Dodge	C2148				8 - 5/64	
330	55-56	(5.4L) Desoto	P2146 C2146	8	3.720	94.50	8 - 5/64 8 - 5/64	8 - 3/16
331	51-56	(5.5L) Chrysler	P2339	8	3.813	96.85	8 - 5/64	8 - 3/16
331	54-56	(5.5L) Dodge	C2339				8 - 5/64	
331	1956	(5.5L) Plymouth						
340	68-73	(5.6L) Dodge, Plymouth	P2277 C2277	8	4.040	102.61	8 - 5/64 8 - 5/64	8 - 3/16
341	1957	(5.6L) Desoto	P2149 C2149	8	3.780	96.00	8 - 5/64 8 - 5/64	8 - 3/16
345	10-15	(5.7L) Dodge Durango Hemi 5.7	S3982	8	3.917	99.50	8 - 1.20	8 - 2.00
345	10-15	(5.7L) Chrysler 300 EZB Hemi 5.7					8 - 1.20	
345	09-15	(5.7L) Dodge Challenger Hemi 5.7						
345	10-15	(5.7L) Dodge Charger Hemi 5.7						
348	03-08	(5.7L) Hemi Vin: D, H, 2	P3975 ⁺ C3975 ⁺	8	3.917	99.50	8 - 1.50 8 - 1.50	8 - 3.00
350	1958	(5.7L) Desoto, Dodge, Plymouth	P2135 C2135	8	4.063	103.19	8 - 5/64 8 - 5/64	8 - 3/16
354	56-58	(5.8L) Chrysler	P3158	8	3.937	100.00	8 - 5/64	8 - 3/16
354	56-59	(5.8L) Dodge	C3158				8 - 5/64	
360	71-80	(5.9L) Plymouth	P2271	8	4.000	101.60	8 - 5/64	8 - 3/16
360	71-95	(5.9L) Dodge	C2271				8 - 5/64	
360	71-84	(5.9L) Chrysler						
360	93-04	(5.9L) Dodge Truck Z	P3915 C3915	8	4.000	101.60	8 - 1.50 8 - 1.50	8 - 4.00
361	59-69	(5.9L) Canada	P2187	8	4.125	104.78	8 - 5/64	8 - 3/16
361	58-61	(5.9L) Desoto	C2187				8 - 5/64	
361	58-66	(5.9L) Dodge, Plymouth						
361	60-76	(5.9L) Dodge Truck	P2995 C2995	8	4.125	104.78	8 - 3/32 8 - 3/32	8 - 3/16

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone

CHRYSLER

Cubic			Set No	Cyl	Bore Diameter		Ring Size	
Inch	Year	Application			Inch	MM	Comp	Oil
383	59-71	(6.3L) Dodge, Plymouth	P2378	8	4.250	107.95	8 - 5/64	8 - 3/16
383	59-61	(6.3L) Desoto	C2378				8 - 5/64	
392	56-58	(6.4L)	P2271 C2271	8	4.000	101.60	8 - 5/64 8 - 5/64	8 - 3/16
400	72-78	(6.6L) Chrysler, Dodge, Plymouth	P3809 C3809	8	4.342	110.28	8 - 5/64 8 - 5/64	8 - 3/16
413	59-66	(6.8L)	P2377	8	4.188	106.36	8 - 5/64	8 - 3/16
413	63-65	(6.8L) Dodge	C2377				8 - 5/64	
413	60-78	(6.8L) Dodge Truck	P2448 C2448	8	4.188	106.36	8 - 3/32 8 - 3/32	8 - 3/16
426	63-71	(7.0L) Dodge, Plymouth	P2378 C2378	8	4.250	107.95	8 - 5/64 8 - 5/64	8 - 3/16
440	66-80	(7.2L) Dodge	P2382	8	4.320	109.70	8 - 5/64	8 - 3/16
440	66-78	(7.2L) Chrysler, Plymouth	C2382				8 - 5/64	
478	70-78	(7.8L) Dodge	P2498 C2498	8	4.500	114.30	8 - 3/32 8 - 3/32	8 - 3/16
488	94-03	(8.0L) Dodge W	P3928 C3928	10	4.000	101.60	10 - 1.50 10 - 1.50	10 - 4.00
549	70-78	(9.0L) Dodge	P2498 C2498	8	4.500	114.30	8 - 3/32 8 - 3/32	8 - 3/16

+ = Contains Ductile Or Steel Ring(s) N = New Number A = Standard Only FK = Full Keystone HK = 1/2 Keystone